

Design and Analysis of Turbomachinery for Space Applications

Dr. Dan Dorney
NASA Marshall Space Flight Center
Applied Fluid Dynamics Analysis Group
October 4, 2002



Overview



- Motivation
- Corsair
- Numerical experiments
 - Two-stage supersonic turbine
 - Partial-admission supersonic turbine
 - Centrifugal pump/diffuser stage
 - SSME fuel feed line/inducer
- Future directions



Motivation



- Incorporate CFD into all aspects of turbomachinery design and analysis
 - Incorporate optimization techniques
 - Reduce design cycle time
- Characterize the unsteady and time-averaged flow fields:
 - Provide unsteady loads for structural/thermal analyses

3



CORSAIR

4



Corsair - I



- Corsair – 3D CFD code for analysis of turbomachinery components
 - 14 years of development
 - Doug Sondak (Boston University) co-author
- Wildcat is the 2D version of Corsair
- Available free from NASA

5



Corsair - II



- Time-dependent equations of motion
 - Full Navier-Stokes, thin-layer Navier-Stokes or Euler
 - Variable fluid properties (C_p , γ) as a function of P , T
- Third-order spatial discretization of inviscid fluxes
 - Roe
- Second-order spatial discretization of viscous fluxes
 - Standard central differences
- Second-order temporal accuracy

6



Corsair - III



- Multi-block O-H grid topology
 - O-grids around airfoils and in tip clearance regions
 - H-grids for remainder of flow field and nozzles
 - Well-suited for parallel simulations
- Grid Motion
 - Arbitrary translation/rotation
 - Blade vibration

7




Corsair - IV




- Turbulence models
 - Highly-modified Baldwin-Lomax model
 - Two-equation models (2D only)
- Transition models
 - Abu-Ghannam and Shaw
 - Mayle
 - Roberts

8




Corsair - V




- Boundary conditions
 - Steady and unsteady inlet and exit
 - Specified wall temperature or heat flux
 - Film cooling/mass injection
 - Symmetry, part-span shrouds
 - Actuator disk
 - Component linking (cavities, etc.)

9



Corsair - VI



- Parallel simulations
 - MPI used for coarse-grain decomposition
 - decomposition by blade row or passage
 - decomposition by O- and H-grids
 - decomposition by component
 - user specified decomposition
 - OpenMP used for fine-grain decomposition

10



Corsair - VII





- Miscellaneous capabilities
 - Internal error checking
 - Conjugate heat transfer capability
 - Provides unsteady pressure files for stress analysis
 - Comprehensive design page
 - Will run on Unix, Linux or Windows NT platforms



11





Design and Analysis of A Two-Stage Supersonic Turbine

12









Simplex Partial-Admission Turbine



- **Simplex supersonic turbine**

- Straight centerline nozzles (6 nozzles/95 rotors)

- **Full-Admission simulation**

- 1 nozzle and 8 rotors modeled, 1.3 million grid points

- **Partial-Admission simulation**

- 6 nozzles and 95 rotors modeled, 7.1 million grid points

- 1+ revolutions

- **Flow conditions**

- $M_1=0.25$, $P_{t1}=801$ psia, $T_{t1}=799$ R, $P_{t1}/P_3=15$

- Operating fluid is GOX in engine, N_2 in rig experiments

- **Computational resources**

- 17-38 MPI processes on 450 MHz SGI O2000 processors


- 1-3 OpenMP threads

- 3×10^{-6} sec/grid point/iteration using 38 MPI process, 1 OpenMP thread

19




Simplex Partial-Admission Turbine



20



Instantaneous Mach Number




FULL ADMISSION

PARTIAL ADMISSION

21



Unsteady Pressure Envelopes







Full Admission



Partial Admission
In and Out of Jets



Partial Admission
In Jets

22












SSME Flow Liner/Inducer Simulations



31







SSME LH2 Feed System







32

















Inducer Simulation w/slots, cavity



Velocity magnitude (ft/sec)



Instantaneous



Time-Averaged (1 rev)


45




Inducer Simulation w/slots, cavity



Time-averaged (over 1 rev) velocity magnitude (ft/sec)







Adjacent Liner



Mid-Cavity

46







Future Directions

51



Current Work and Future Plans



- “All-speed” version of Corsair (Phantom)
 - Reformulate equations without perfect gas assumption
 - Primitive variable formulation
 - Tabular fluid properties or compute based on equation of state
 - Sensors to switch between incompressible (pre-conditioning) and compressible physics
 - Dual time stepping to replace Newton iterations for time accuracy
- Two-phase flows
- Cavitation modeling
 - Necessary for accurate pump/inducer design and analysis

52